

FEATURES AND SPECIFICATIONS

Features and Benefits

- Sizes 2 to 25 circuits
- Locking crown secures positive latch to header
- Polarization slots guide front ribs of mating connector to prevent pin damage
- Standoffs minimize flux retention
- Surface Mount Compatible

Reference Information

Product Specification: PS-70541

Packaging: Tube

UL File No.: E29179

CSA File No.: LR19980

Mates With: 70066G, 70066N, 70400G and 70430G

Designed In: Inches

Electrical

Voltage: 250V

Current: 3.0A

Contact Resistance: 15mΩ max.

Dielectric Withstanding Voltage: 1500V

Insulation Resistance: 1000 MΩ min.

Mechanical

Durability: 25 cycles Tin and 50 cycles Gold

Physical

Housing: Black glass-filled PCT, UL 94V-0

Contact: Phosphor Bronze, .025" square

Plating: See Table

Operating Temperature: -40 to +105°C




2.54mm (.100") Pitch

SL™

Wire-to-Board Shrouded Header

70553


Single Row, .120" Pocket Right Angle, Low Profile



2.54mm (.100") Pitch

CATALOG DRAWING (FOR REFERENCE ONLY)

Not For Use With C-Grid III™ Components



ORDERING INFORMATION AND DIMENSIONS

Circuits	Order No.			Dimension	
	15μ" Min. Gold	30μ" Min. Gold	150μ" Tin/Lead	A	B
2	• 70553-0001	70553-0106	70553-0036	7.37 (.290)	2.54 (.100)
3	• 70553-0002	70553-0107	70553-0037	10.17 (.400)	5.08 (.200)
4	• 70553-0003	70553-0108	70553-0038	12.71 (.500)	7.62 (.300)
5	• 70553-0004	70553-0109	70553-0039	15.25 (.600)	10.16 (.400)
6	• 70553-0005	70553-0110	70553-0040	17.79 (.700)	12.70 (.500)
7	• 70553-0006	70553-0111	70553-0041	20.33 (.800)	15.24 (.600)
8	• 70553-0007	70553-0112	70553-0042	22.87 (.900)	17.78 (.700)
9	• 70553-0008	70553-0113	70553-0043	25.41 (1.000)	20.32 (.800)
10	• 70553-0009	70553-0114	70553-0044	27.95 (1.100)	22.86 (.900)
11	• 70553-0010	70553-0115	70553-0045	30.49 (1.200)	25.40 (1.000)
12	• 70553-0011	70553-0116	70553-0046	33.03 (1.300)	27.94 (1.100)
13	• 70553-0012	70553-0117	70553-0047	35.57 (1.400)	30.48 (1.200)

Circuits	Order No.			Dimension	
	15μ" Min. Gold	30μ" Min. Gold	150μ" Tin/Lead	A	B
14	• 70553-0013	70553-0118	70553-0048	38.11 (1.500)	33.02 (1.300)
15	• 70553-0014	70553-0119	70553-0049	40.65 (1.600)	35.56 (1.400)
16	• 70553-0015	70553-0120	70553-0050	43.19 (1.700)	38.10 (1.500)
17	• 70553-0016	70553-0121	70553-0051	45.73 (1.800)	40.64 (1.600)
18	• 70553-0017	70553-0122	70553-0052	48.27 (1.900)	43.18 (1.700)
19	• 70553-0018	70553-0123	70553-0053	50.81 (2.000)	45.72 (1.800)
20	• 70553-0019	70553-0124	70553-0054	53.35 (2.100)	48.26 (1.900)
21	• 70553-0020	70553-0125	70553-0055	55.89 (2.200)	50.80 (2.000)
22	• 70553-0021	70553-0126	70553-0056	58.43 (2.300)	53.34 (2.100)
23	• 70553-0022	70553-0127	70553-0057	60.97 (2.400)	55.88 (2.200)
24	• 70553-0023	70553-0128	70553-0058	63.51 (2.500)	58.42 (2.300)
25	• 70553-0024	70553-0129	70553-0059	66.05 (2.600)	60.96 (2.400)

• US Standard Product, available through Molex franchised distributors