


TEST LEVEL	TEST SPECIFICATIONS 70282-4			TEST RESULTS			SERIAL NO.		
	TEST POINT	TEST PARAMETER	LIMIT/UNIT						
X	Fc	Center Frequency	MC	48	72	95			
X	"	Insertion Loss	1.5 DB Max	.2	1.1	1.0			
X	VSWR = 1.5:1	Upper Limit	MC	49	75.2	96.4			
X	"	Lower Limit	MC	46.9	70.6	93.6			
X	"	Bandwidth	MC	2.1	2.6	2.8			
X	"	Bandwidth	%	4.4	3.6	2.9			
X	3 DB Rel,	Upper Limit	MC	49.4	75.7	96.9			
X	"	Lower Limit	MC	46.7	70.2	93.0			
X	"	Bandwidth	MC	2.7	3.5	3.9			
X	"	Bandwidth	5 ± 1%	5.6	4.9	4.1			
X	30 DB	Upper Limit	MC	50.4	75.1	98.7			
X	"	Lower Limit	MC	45.2	68.2	91			
X	"	Bandwidth	MC	5.2	6.9	7.7			
X	30DB BW/3DB BW	Form Factor	2.5 Max.	1.9	2.0	2.0			
X	Fc	Dial Error	+ 1% Max.	✓	✓	✓			

F.A.	1/10T	100%	GOVT SOURCE INSP.		TELONIC ACCEPTANCE		INSP.	DATE	INSP.	DATE
			YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>	STAMP	INSP. 				
TELONIC MODEL NO.			REL. TO PROD. <i>UPP</i> <i>4/27/67</i>			C-5745		MAR 21 1977		
TTF-72-5-5EE			WORK ORDER NO.			INSPECTION REPORT			REPORT NO.	
131697-1			ENGR. <i>Walden</i>			DATE 11-8-68			LAGUNA BEACH, CALIF.	
CUSTOMER DRAWING NO.			REV.			INSPECTION REPORT			REPORT NO.	
						Telonic® ENGINEERING CORP.			31697	